

TOTAL CLASSIC 10W-40



“TOTAL CLASSIC, the guaranteed quality”

Synthetic based multigrade oil for gasoline and diesel engines, formulation using a set of additives with carefully selected performance and proportions to answer to the quality standards of the Association of the European Manufacturers.

APPLICATIONS

Gasoline and Diesel

- Lubrication of all Gasoline engines with or without catalytic converters, and Diesel engines, turbo-charged or naturally aspirated, in cars and light vans in the most varied weather and service conditions.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications

ACEA
API

A3/B4
SL/CF

CUSTOMER BENEFITS

Multigrade properties

- Retains its multigrade properties throughout its life.

Stability

- Good thermal stability.
- Detergent, dispersant, anti-oxidant and anti-corrosion capabilities that easily exceed the requirements of the specifications indicated above.

Anti-wear

- Enhanced anti-wear capability satisfying the requirements of the motor manufacturers.

Cold starting

- Excellent low temperature flow properties ensuring easy cold starts. Engine components are lubricated immediately, giving longer life.

CHARACTERISTICS

TOTAL CLASSIC 10W-40	Units	SAE Grade 10W-40
Density at 15°C	kg/m ³	871
Viscosity at 40°C	mm ² /s	96.66
Viscosity at 100°C	mm ² /s	14,45
Viscosity index	-	155
Flash point Cleveland	°C	238
Pour point	°C	- 42

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS

Le Spazio, 562 avenue du Parc de l'île
92029 Nanterre Cedex
FRANCE
1/1

TOTAL CLASSIC 10W-40
Sheet updated : 02/14



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.